



IFC Cabinets

Integrated Frame Cabinets and Optional Kits

With focus on streamlined assembly, multi-functional use and optionally flat-packed transportation, Eltek has developed a new series of indoor cabinets. The result is a very innovative design.

IFC CABINETS

Doc 900241.DS3 - rev6

APPLICATIONS

The cabinets are designed to meet challenging requirements for indoor Telecom applications, with special focus on cable management, with or without back up batteries.

PRODUCT DESCRIPTION

The indoor IFC cabinet platform offers flexible, modular assembly, using a selection of various options. The range consists of several cabinet variants, enabling multifunctional use.

AVAILABLE MODELS:

- 0,7m Cabinet, W600 x D400
- 1,0m Cabinet, W600 x D400
- 1,2m Cabinet, W600 x D600
- 1,5m Cabinet, W600 x D600
- 1,8m Cabinet, W600 x D400 / D600
- 2,0m Cabinet, W600 x D400 / D600
- 2,2m Cabinet, W600 x D600

KEY FEATURES

- LIGHT WEIGHT (<50KG)
- VERY FLEXIBLE
- FEW BASE ELEMENTS
 - Side wall (identical left and right)
 - Top cover
 - Rear wall
 - Bottom including "toolbox"
 - Battery shelves
 - Adjustable legs
- STEEL OR PAINT FINISH
 - FLEXIBLE SHIPMENT - Shipped assembled
 - Optionally flat-packed to the site
- Assembly time under 20 minutes
- SEISMIC RESISTANCE
 - Meets Zone 4 seismic requirements with optional add-on kits

IFC CABINETS



AND OPTIONAL KITS

Doc 900241.DS3 - rev6

	0,7m	1,0m	1,2m	1,5m	1,8m	2,0m	2,2m
MODEL	W600xD400	W600xD400	W600xD600	W600xD600		W600xD400 W600xD600	W600xD600
PHYSICAL SPECIFI	CATION						
Height	714mm	1025mm	1203mm	1465mm	1780mm	1960mm	2180mm
Width	596mm	596mm	596mm	596mm	596mm	596mm	596mm
Depth without the door ¹⁾	407mm	407mm	607mm	607mm	407 / 607mm	407 / 607mm	607mm
Weight ²⁾	14kg	19kg	25kg	28kg	24,5 / 31,5kg	25,5 / 34kg	36,5kg
Rack space	13U (wall mount) 14U (floor mount)	21U	25U	31U	38U	43U	47U
ALL MODELS							
CONSTRUCTION							
Material	Galvanized stee	l 0,7mm thicknes	s, self-bearing c	onstruction			
Finish	Steel finish (not painted) Black colour powder coated, RAL 9005						
Top knock-outs	5x PG21 5x PG28						
Rack installation width	23inch						
Adjustable feet	Adjustable feet, to easily level the cabinet.						
Cabinet grounding	Cabinet grounding is provided via two M6 grounding point.						
Toolbox	Cabinet comes with toolbox feature located at bottom under battery shelf; it includes lifting ears, wall fixing brackets and other necessities						
Weight capacity	Maximum weigh	t capacity of cab	inet is 1350kg p	er cabinet.			
FRONT COVER OPT	TIONS						
Door	Fully vented door, hinged on left or right side of the cabinet secured with two locks allowing 150 degree opening for good access during installation						
Battery cover	Easily detachable battery section cover						
Front panels	Various vented a	and blind front se	ection panels				
MISCELLANEOUS O							
19inch mounting rails	23 to 19inch mounting rails in various lengths						
Support shelf	Equipment supp						
Battery shelf	Battery shelf to hold a string of batteries with maximum configuration of five (5) battery shelves per cabinet Maximum weight load 270kg per battery shelf Meets Zone 4 seismic requirements with optional add-on kits						
Seismic option	Meets Zone 4 se	eismic requirement	nts with optiona	l add-on kits			
DESIGN STANDARI							
Safety	IEC 60950-1:200		2006+A11:2009				
Transportation	ETSI EN 300-019)-2					
Ingress Protection	IP20 when proper par	nels are installed					
ORDERING INFORM	IATION						
Part No.	Description			M	DQ		
Cxxxxxx.nnnn	Cabinet with pov (to be ordered th	wer system nrough Creator or C	ustom project)	1			
	nal 28mm to cabine ont covers and opti						
oc 900241.DS3 – rev6					Specifications a	are subject to chang	ge without notice